

Standard Analog Video Cable

RG-59/U Type



Description	Part No.	UL NEC/ C(UL) CEC Type	Standard Lengths		Standard Unit Weight		Conductor (stranding) Diameter Nom. DCR	Nominal Core OD		Shielding Materials Nom. DCR	Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation		
			Ft.	m	Lbs.	kg		Inch	mm		Inch	mm			pF/Ft.	pF/m	MHz	dB/ 100 Ft.	dB/ 100m

23 AWG Solid .023" Bare Copper or Bare Copper-covered Steel Conductor (see below) • Bare Copper Braid Shield (95% Coverage)

Polyethylene Insulation • Black PVC Jacket																			
UL AWM Style 1354 (30V 75°C) VW-1	8241	NEC: CM	100	30.5	4.4	2.0	23 AWG (solid) .023"	.146	3.71	BC Braid 95% Shield Coverage	.240	6.10	75	66%	20.5	67.3	1	6	2.0
		CEC: CMG FT4	U-500	U-152.4	19.5	8.9	BCCS 2.6Ω/M'			8.5Ω/km							10	1.1	3.6
			500	152.4	18.5	8.4	49.0Ω/M'										50	2.4	7.9
			U-1000*	U-304.8	38.0	17.2	160.7Ω/km										100	3.4	11.2
			1000	304.8	40.0	18.1											200	4.9	16.1
			2000	609.6	80.0	36.3											400	7.0	23.0
			5000	1524.0	200.0	90.7											700	9.7	31.8
																	900	11.1	36.4
																	1000	12.0	39.4

*U-1000 ft. put-up also available in Red, Yellow, Green, Lt. Blue, White or Orange.

Flame-retardant Semi-foam Polyethylene Insulation • Black PVC Jacket																			
UL AWM Style 1354 (30V 75°C)	8241A	NEC: CMG CEC: CMG FT4	U-1000	U-304.8	40.0	18.1	23 AWG (solid) .023"	.146	3.71	BC Braid 95% Shield Coverage	.242	6.15	75	66%	20.5	67.3	1	6	2.0
			1000	304.8	42.0	19.1	BCCS 2.6Ω/M'			8.5Ω/km							5	9	3.0
							49.0Ω/M'										10	1.1	3.6
							160.7Ω/km										50	2.4	7.9
																	100	3.4	11.2
																	200	4.9	16.1
																	400	7.0	23.0
																	700	10.1	33.1
																	900	11.7	38.4
																	1000	13.2	43.3

Suitable for Indoor and Outdoor applications.

Polyethylene Insulation • Black PVC Jacket																			
UL AWM Style 1354 (30V 80°C)	8241B	NEC: CM CEC: CM	U-1000	U-304.8	36.0	16.3	23 AWG (solid) .023"	.146	3.71	BC Braid 95% Shield Coverage	.242	6.15	75	66%	20.5	67.3	1	4	1.3
			1000	304.8	37.0	16.8	BC 2.9Ω/M'			9.5Ω/km							10	1.1	3.6
							20.4Ω/M'										50	2.4	7.9
							66.9Ω/km										100	3.4	11.2
																	200	4.9	16.1
																	400	7.0	23.0
																	700	9.7	31.8
																	900	11.1	36.4
																	1000	12.0	39.4

Suitable for Indoor and Outdoor applications.

22 AWG Stranded (7x30) .030" Bare Copper Conductor • Bare Copper Braid Shield (95% Coverage)

Foam Polyethylene Insulation • PVC Jacket (Available in Matte Black, Red, Blue, Green, White, Gray or Yellow)																			
High-Flex 60°C	8241F	—	1000	304.8	35.0	15.9	22 AWG (7x30) .030"	.146	3.71	BC Braid 95% Shield Coverage	.242	6.15	75	78%	17.3	56.8	1	3	1.0
							BC 15.0Ω/M'			8.5Ω/km							10	9	3.0
							49.2Ω/km										50	2.1	6.9
																	100	3.0	9.8
																	200	4.5	14.8
																	400	6.6	21.7
																	700	8.9	29.2
																	900	10.1	33.1
																	1000	10.9	35.8

23 AWG Solid .023" Bare Copper-covered Steel Conductor • Bare Copper Braid Shield (97% Coverage)

Plenum • FEP Insulation • Black FEP Jacket																			
200°C	88241	NEC: CMP CEC: CMP FT6	500†	152.4	18.0	8.2	23 AWG (solid) .023"	.132	3.35	BC Braid 97% Shield Coverage	.190	4.83	75	69.5%	19.5	64.0	1	5	1.6
			1000†	304.8	36.0	16.3	BCCS 2.6Ω/M'			8.5Ω/km							10	1.0	3.3
							49.0Ω/M'										50	2.3	7.5
							160.7Ω/km										100	3.3	10.8
																	200	5.2	17.1
																	400	8.4	27.6
																	700	11.6	38.0
																	900	13.8	45.3
																	1000	14.8	48.6

Suitable for Outdoor and Direct Burial applications.

Plenum • FEP Insulation • Natural Flammarrest® Jacket																			
75°C	82241	NEC: CMP CEC: CMP FT6	U-500†	U-152.4	18.5	8.4	23 AWG (solid) .023"	.134	3.35	BC Braid 97% Shield Coverage	.190	4.83	75	69.5%	19.5	64.0	1	5	1.6
			U-1000†	U-304.8	36.0	16.3	BCCS 2.6Ω/M'			8.5Ω/km							10	1.0	3.3
			1000†	304.8	34.0	15.4	49.0Ω/M'										50	2.3	7.5
							160.7Ω/km										100	3.3	10.8
																	200	5.2	17.1
																	400	8.4	27.6
																	700	11.6	38.0
																	900	13.8	45.3
																	1000	14.8	48.6

BC = Bare Copper • BCCS = Bare Copper-covered Steel • DCR = DC Resistance • FEP = Fluorinated Ethylene Propylene

Contact the Belden Customer Service Department for a Comprehensive Connector Cross Reference. 1-800-BELDEN-1. Request quotations of RG/U cables not listed.

†Spools and/or UnReel® cartons are one piece, but length may vary ±10% from length shown.



For more information, contact Belden Technical Support: 1-800-BELDEN-1 • www.belden.com