





GENERAL-PURPOSE MICRO SWITCH

Z-15 Series

SPECIFICATIONS:

- Terminal: Screw terminal
- Contact resistance: 15mΩ maximum. (Initial)
- Insulation resistance: 100MΩ minimum. (At 500VDC)
- Dielectric strength: 1,000VAC 50/60Hz for 1 minute.
- Contact configuration:  15A 125VAC Or 250VAC
1/2A 125VDC, 1/4A 250VDC
1/8HP 125VAC 1/4HP 250VAC
- Service life: Mechanically: 1,000,000 operations minimum.
Electrically: 100,000 operations minimum.



★ SOLDER TYPES

Technical drawings and dimensions for various Z-15 Series models:

- Z-15GL2**: Dimensions include 46.10, 1.0, 25.4±0.1, 11.9, 17.45, 49.2.
- Z-15GL**: Dimensions include 49.6±0.8, 1.0, 25.4±0.1, 11.9, 49.2, 4.8, 17.45.
- Z-15G**: Dimensions include 23.3±0.25, 25.4±0.1, 11.9, 49.2, 17.45.
- Z-15GQ**: Dimensions include 23.3±0.25, 11.9, 17.45, 49.2.
- Z-15GQ22**: Dimensions include 23.3±0.25, 49.2.
- Z-15GW1**: Dimensions include 23.3±0.25, 49.2.
- Z-15GW2**: Dimensions include 23.3±0.25, 49.2.
- Z-15GW2277**: Dimensions include 23.3±0.25, 49.2.

