

## Specifications

### Environmental and Regulatory Specifications

Operating temperature	0°C – 40°C (32°F – 104°F)
Operating relative humidity (% RH without condensation)	95% (10°C – 35°C ; 50°F – 95°F) 75% (35°C – 40°C ; 95°F – 104°F) uncontrolled < 50°F (10°C)
Altitude	3000 m
EMC	EN 55022, EN 55024

### MT-7068-T Toner

Tone frequency	1KHz
Tone mode	One-note / Two-note
Output power	15.5Vp-p
Compatible connectors	RJ-45/RJ-11/USB/F/BNC/RCA/Alligator Clips
Continuity test	<300Ω
Talk battery voltage	6V into 600Ω
Function selection	5-position rotary switch
Cable Map Indication	8 LED indicators
Voltage protection	100V
Low battery display	5.5V
Battery type	9V (6F22)
Dimension (LxWxD)	140x70x36mm
Weight	203g (with battery)

### MT-7068-R Probe

Frequency	1KHz
Compatible connectors	RJ-45/RJ-11/USB/F/BNC/RCA
Ear jack	1
Signal status indication	8 LED indicators
Cable map indication	8 LED indicators
Low battery display	5.5V
Battery type	9V (6F22)
Dimension (LxWxD)	250x52x33mm
Weight	190g (with battery)