



DJM Monitor Boxes For Temperature Controllers



A QUALITY PRODUCT

EXPLOSIONPROOF

For UL.60079-1 Standard Class I, II Div. 2 Groups C,D,E,F and G

For IEC.60079-0/1 Standard Zone 2



ISO9001:2008

Technical data

- Type of Protection: Ex d IIA T6
- Conforming to : Standards IEC 60079-1 or UL 60079-0/1
- Marking for test : Ex II2G
- Degree of Protection : IP66 acc.To IEC 60529
- Ambient Temp. (Ta) : -20°C to+ 55°C Temp.class T6
- Type :DJM
- Protection class for UL. : Class I, Division 1, 2 Group.C,D
 Class II, Division 1 or 2 Groups.E,F,G
 Class III
- Protection class for IEC : Zone 1 , 2
- Cable Gland : PG9 and PG6
- Contact rating 220V.AC.



DJM

Specification

- Body,Cover : Copper-free aluminium alloy with epoxy-polyester powder coated.
- Seal gasket : Silicone -40°C to +175°C
- Lens : Heat and impact resistant glass

Catalogue Nubmer:

| Cat. No. | Cable Gland | | Dimension in mm. | | | | | Approx. Weight (kgs.) |
|--------------|----------------------|--------|------------------|----|-----|----|-----|--------------------------|
| | Outer Diameter (mm.) | | a | b | c | d | e | |
| | PG6 | PG9 | | | | | | |
| DJM - VD2003 | 4. - 7 | 5. - 9 | 156 | 88 | 114 | 44 | 157 | 2 |

Remark:

In case the enclosures are supplied completely with control units or devices, They will be delivered with conformity certificate and can be used without further testing. supply temperature controllers for VD-2003 series and Vertex brand.

Catalogue Nubmer:

