



A QUALITY PRODUCT

EEM Emergency Push Buttons

EXPLOSIONPROOF

For UL.60079-1 Standard Class I, II Div. 2 Groups C,D,E,F and G

For IEC.60079-0/1 Standard Zone 2

● Technical data

Type of Protection: Ex ed IIA T6

Conforming to : Standards IEC 60079-1 or UL 60079-0/1

Marking for test : Ex II2G

Degree of Protection : IP65 acc.To IEC 60529

Ambient Temp. (Ta) : -20 °C to + 55 °C Temp.class T5 - T6

Type :EEM

Protection class for UL. : Class I, Division 2 Group.C,D

Class II, Division 1 or 2 Groups.E,F,G

Class III

Protection class for IEC : Zone 2

Conduit hub : 1/2" NPT.



EEM 11 L

● Specification:

- Body , Cover : Copper-free aluminium with epoxy - polyester powder coated.
- Seal gasket : NBR rubber -40° C to + 175° C
- Bolts : Stainless steel

● Catalogue Nubmer:

Number of contact	Symbol	Nameplate Marking	Cat.,No.
			Dead-end (1 hub)
Momentary			
1NC		EMERGENCY STOP	EEM 01
1NO-1NC		EMERGENCY STOP	EEM 11
Push - Lock , Turn - Reset			
1NC		EMERGENCY STOP	EEM 01L
1NO-1NC		EMERGENCY STOP	EEM 11L

Dimensions: (in mm.)

