



# SEALED LEAD ACID CALCIUM BATTERY DATA SHEET

## HGL1.3-12



### Applications:

- UPS power systems
- Portable Electronic Instruments
- Emergency Lighting Systems
- Mining Search Light Products
- Portable Camping Equipments
- Remote Scientific Instruments

### Electrical Specification

Capacity	Load	Duration	Final Voltage
<b>Rated Capacity @ 25 °C (77 °F)</b>			
1.30Ah	0.07A	20 Hours	10.50V
1.21Ah	0.12A	10 Hours	10.20V
1.11Ah	0.22A	5 Hours	10.02V
0.78Ah	0.78A	1 Hour	9.60V
0.65Ah	1.30A	0.5 Hour	9.00V

### Physical Specification

Length	Width	Height	Overall Height
3.82 in	1.69 in	2.05 in	2.24 in
97 mm	43 mm	52 mm	57 mm
Internal Resistance@25°C Fully Charged			39 MΩ

**Weight:** 0.62 Kg.  
**Case Material:** ABS

### Capacity ~ Temperature

104°F(40°C)	77°F(25°C)	32°F(0°C)	5°F(-15°C)
102%	100%	85%	65%

### Self Discharge

4 Mo. 20°C	8 Mo. 20°C	4 Mo. 30°C	8 Mo. 30°C
14%	26%	24%	40%

### Charging - Constant Voltage

@25°C (77°F)	Standby Usage:	Cyclic Usage:
<b>Voltage</b>	13.6 ~ 13.8V	14.4 ~ 14.8V
<b>Current</b>	0.13~0.16A	0.13~0.16A
<b>Current (max.)</b>	N/A	0.26

### Life Expectancy

Standby Usage:	@25 °C	3 ~ 4 Years
<b>Cyclic Usage:</b>	100% Discharged	200 ~ 250 Cycles
	50% Discharged	500 ~ 600 Cycles
	30% Discharged	1,100 ~ 1,200 Cycles