

VALVE-REGULATED LEAD ACID BATTERIES: INDIVIDUAL DATA SHEET

LC-RD1217P

Panasonic


For main and standby power supplies. Expected trickle life: Approx 3-5 years at 25°C, Approx. 5 years at 20°C.

Dimensions (mm)

Terminal type: LC-RD1217P: M5 bolt and nut



Photo/Label for reference only.




Specifications

Nominal Voltage		12V
Rated Capacity (20 hour rate)		17Ah
Dimensions	Length	7.126 inches (181.0 mm)
	Width	2.992 inches (76.0 mm)
	Height	6.575 inches (167.0 mm)
	Total Height	6.575 inches (167.0 mm)
Approx. mass		14.34 lbs. (6.5 kg)
Standard Terminals and Resin	UL94HB M5 Bolt and Nut	LC-RD1217P

Battery case resin: Standard (UL94HB) Color is black.


Discharge characteristics 77 °F (25 °C)^(Note)



Characteristics

Capacity (note) 77°F (25°C)	20 hour rate (850mA)	17Ah	
	10 hour rate (1500mA)	15Ah	
	5 hour rate (2600mA)	13Ah	
	1 hour rate (10000mA)	10Ah	
	1.5 hour rate discharge Cut-off voltage 10.5 V	7A	
Internal resistance	Fully charged battery 77°F (25°C)	Approx. 12mΩ	
Temperature dependency of capacity (20 hour rate)	104°F (40°C)	102%	
	77°F (25°C)	100%	
	32°F (0°C)	85%	
Self discharge 77°F (25°C)	Residual capacity after standing 3 months	91%	
	Residual capacity after standing 6 months	82%	
	Residual capacity after standing 12 months	64%	
Charge Method (Constant Voltage)	Cycle use (Repeating use)	Initial current	6.8 A or smaller
		Control voltage	14.5V to 14.9V (per 12V cell 25°C)
	Trickle use	Initial current	2.55 A or smaller
		Control voltage	13.6V to 13.8V (per 12V cell 25°C)

Duration of discharge vs. Discharge current ^(Note)



(Note) The above characteristics data are average values obtained within three charge/discharge. Cycles not the minimum values.

(Note) For cycle use of the battery, please contact us in advance.



Siam Battery Electronic Limited Partnership

Tel. 02-913-0750, 02-587-7780 Fax. 02-587-1624

E-mail: sale@SiamBat.com www.SiamBat.com