

LP SERIES-General Purpose

LP12-7.8 (12V7.8AH)


Specification

Nominal Voltage	12V	
Nominal Capacity(20HR)	7.8AH	
Dimension	Length	151±1mm (5.95 inches)
	Width	65±1mm (2.56 inches)
	Container Height	94.5±1mm (3.72 inches)
	Total Height (with Terminal)	100±1mm (3.94 inches)
Approx Weight	Approx 2.5 kg (5.51lbs)	
Terminal	T1 / T2	
Container Material	ABS	
Rated Capacity	7.80 AH/0.39A	(20hr , 1.80V/cell,25°C/77°F)
	7.25 AH/0.72A	(10hr, 1.80V/cell,25°C/77°F)
	6.63 AH/1.33A	(5hr, 1.75V/cell,25°C/77°F)
	5.96 AH/1.99A	(3hr, 1.75V/cell,25°C/77°F)
	4.90 AH/4.90A	(1hr, 1.60V/cell,25°C/77°F)
Max. Discharge Current	117A (5s)	
Internal Resistance	Approx 18mΩ	
Operating Temp.Range	Discharge : -15~50°C (5~122°F)	
	Charge : 0~40°C (32~104°F)	
	Storage : -15~40°C (5~104°F)	
Nominal Operating Temp. Range	25±3°C (77±5°F)	
Cycle Use	Initial Charging Current less than2.34A.Voltage	
	14.4V~15.0V at 25°C(77°F)Temp. Coefficient -30mV/°C	
Standby Use	No limit on Initial Charging Current Voltage	
	13.5V~13.8V at 25°C(77°F)Temp. Coefficient -20mV/°C	
Capacity affected by Temperature	40°C (104°F)	103%
	25°C (77°F)	100%
	0°C (32°F)	86%
Self Discharge	Leoch LP series batterys may be stored for up to 6 months at 25°C(77°F) and then a freshening charge is required. For higher temperatures the time interval will be shorter.	



Applications

- ◆ All purpose
- ◆ Uninterruptable Power Supply (UPS)
- ◆ Electric Power System (EPS)
- ◆ Emergency backup power supply
- ◆ Emergency light
- ◆ Railway signal
- ◆ Aircraft signal
- ◆ Alarm and security system
- ◆ Electronic apparatus and equipment
- ◆ Communication power supply
- ◆ DC power supply
- ◆ Auto control system



Constant Current Discharge (Amperes) at 25 °C (77°F)

F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	14.9	11.4	9.45	8.17	6.32	4.65	3.92	2.32	1.82	1.48	1.20	1.04	0.842	0.704	0.386
1.80V/cell	19.9	14.6	11.4	9.7	7.45	5.41	4.39	2.53	1.95	1.58	1.29	1.12	0.893	0.725	0.390
1.75V/cell	22.5	16.0	12.5	10.4	7.74	5.62	4.60	2.63	1.99	1.61	1.33	1.15	0.909	0.745	0.394
1.70V/cell	24.8	17.5	13.3	10.9	8.05	5.84	4.74	2.69	2.04	1.65	1.36	1.17	0.921	0.760	0.401
1.65V/cell	27.3	18.8	14.2	11.6	8.50	5.99	4.85	2.73	2.13	1.71	1.40	1.20	0.936	0.775	0.406
1.60V/cell	30.1	20.5	15.1	12.4	8.97	6.24	4.90	2.85	2.20	1.76	1.44	1.23	0.945	0.784	0.409




Constant Power Discharge (Watts) at 25 °C (77°F)

F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	27.16	21.07	17.63	15.40	12.04	8.94	7.57	4.50	3.54	2.89	2.36	2.05	1.66	1.39	0.765
1.80V/cell	36.07	26.61	21.02	17.94	13.99	10.32	8.43	4.88	3.79	3.06	2.52	2.19	1.76	1.43	0.771
1.75V/cell	39.80	28.77	22.67	19.11	14.40	10.61	8.78	5.05	3.84	3.12	2.58	2.25	1.78	1.47	0.778
1.70V/cell	42.61	30.64	23.87	19.93	14.91	10.99	9.03	5.16	3.94	3.20	2.64	2.29	1.81	1.50	0.792
1.65V/cell	46.32	32.77	25.19	21.02	15.60	11.17	9.17	5.21	4.09	3.30	2.70	2.33	1.83	1.53	0.801
1.60V/cell	49.91	34.76	26.49	22.14	16.35	11.58	9.21	5.40	4.20	3.39	2.78	2.38	1.85	1.54	0.805


Dimensions

T1 Terminal


Unit: mm [inches]




Discharge Characteristics




Float Charging Characteristics




Temperature Effects in Relation to Battery Capacity




Effect of Temperature on Long Term Float Life



Cycle Life in Relation to Depth of Discharge



Self Discharge Characteristics



Sales Office

China sales office:

Add: 5th Floor, Xinbaohui Bldg., Nanshan, Shenzhen, China. 518052
Tel: +86-755-86036060 (100 lines)
Fax: +86-755-26067269
E-mail: export@leoch.com
Http://www.leoch.com

North America sales office:

Add: 19751 Descartes, Unit A, Foothill Ranch, CA 92610, USA
Tel: 949-588-5853
Fax: 949-588-5966
E-mail: sales@leoch.us
Http://www.leoch.us

Europe sales office:

Add: La Campagna House, Main Road, Gloucester, GL2-8JH, United Kingdom
Tel: +44(0) 1452 751016
E-mail: Sales.Europe@leoch.com
Http://www.leoch.com