

FCT-3G 1FXS**3G Fixed Wireless Terminal FCT-3G****Dual Line**
2xRJ-11**Triple-band**
850/1900/2100 MHz**Back-UP**
Battery**MORE****Technical specifications****3G/GSM parameters**

Support: HSDPA/UMTS/EDGE/GPRS/GSM

Triple-band HSDPA (UMTS): 850/1900/2100MHz

HSDPA downlink: 3.6Mbps

WCDMA (UMTS) uplink: 384kbps

EDGE data: 237kbps downlink and 118kbps uplink

GPRS data: 85.6kbps downlink and 42.8kbps uplink

**INTRODUCTION:****Main Features**

1. Convert phone call from fixed line to 3G Wireless Network
2. 2x RJ-11 phone ports for connecting phone, PABX or VoIP Gateway
3. Support SIM Lock and Network Lock
4. External Antenna connector - SMA Type
5. Optional back-up battery
6. Volume adjustment and echo cancel
7. Support caller ID: DTMF Mode; optional FSK Caller ID
8. Reverse Polarity or 12/16 KHz metering signal
9. USB port to connect PC for 3G Data network (HSDPA/UMTS);

Power supply

AC input voltage: 100V~240V AC

Power adaptor output: DC9V/1.5A

Battery: 6V/4AH Lead-Acid battery optional

Maximum charging current: 600MA

DC input voltage range: 9V~10V DC

Maximum working current: 700ma (DC7.5V,

Average current, excluding charger current)

Application environment

Operating temperature: 0~+50° C

Relative humidity: 10%~90%