

Affordable and Easy-to-use

- TI TITAN chipset and TI voice engine
- 2 programmable keys, Auto provision
- 1xLAN, 1xdual-color LED, Phone label
- Power over Ethernet, Wall-mountable



The SIP-T18P is the simply IP phone that equipped with TI TITAN chipset, comprehensive telephony features, PoE, auto provision, and interoperable with the leading IP-PBX and soft switch. It is economical and can be desktop or wall mounted.

Designed for working environment needing a basic feature IP phone, the SIP-T18P is a very cost-effective choice for small business, SOHO and Hotel, college apartment, supermarket, and warehouse etc.

Phone Features

- 1 VoIP account, Hotline
- Call waiting, Call transfer, Call forward
- Call hold, Mute, Redial, DND
- 3-way conferencing, Speed dial
- Direct IP call without SIP proxy
- Volume control, Ringtone selection
- Tone scheme, System log export
- Integrated Voice Response System

IP PBX System Integration

- Music on hold
- Call park, Call pickup
- Dial plan, Dial now
- Voicemail
- Message Waiting Indication (MWI)
- Distinctive ringtone

Voice Features

- Wideband codec: G.722
- Narrowband codec: G.711 μ /A, G.726, G.729AB, G.723.1
- VAD, CNG, PLC, AJB, AGC

Network Features

- SIP v1 (RFC2543), v2 (RFC3261)
- NAT Traversal: STUN mode
- DTMF: In-band, out-of band (RFC2833) and SIP INFO
- Proxy mode and peer-to-peer SIP link mode
- IP Assignment: Static/DHCP
- TFTP/DHCP client
- Telnet/HTTP server
- DNS client

Management

- Built-in HTTP web server
- Configuration: browser/phone/auto-provision/IVR
- Auto provision via TFTP/FTP/HTTP/PnP
- Auto provision for firmware, configuration, ringtone etc

Security

- QoS: IEEE 802.1p/q tagging (VLAN), Layer 3ToS
- Digest authentication using MD5/MD5-sess
- Secure configuration file via AES encryption
- Admin/user configuration mode

Physical Features

- TI TITAN chipset
- 20 keys including 2 programmable keys
- 4 feature keys (Transfer/Hold/Mute/Redial)
- Phone label
- 1xdual-color LED
- 1xRJ45 10/100M Ethernet port
- Desktop with footstand (detachable), Wall-mountable
- Power adapter: AC 100~240V input and DC 5V/1.2A Output
- Power over Ethernet (IEEE 802.3af class 1) optional
- Operating humidity: 10~95%
- Storage temperature: up to 60°C

Package Features

- Qty/CTN: 10 PCS
- N.W/CTN: xx KG
- G.W/CTN: xx KG
- Measurement: 0.054CMB
- Carton Meas: 520x470x220MM

Certifications

